

travelvolts

Cable set for compressor fridge

CAUTION

DISCONNECT LEISURE BATTERY NEGATIVE CABLE BEFORE FITTING

This cable should be connected directly to the leisure battery or to a fuse box with at least 6 mm csa supply cable. Do not insert any switches in this cable otherwise your fridge will under perform.

The cable is supplied with spade connectors to facilitate connection directly to the control box on the fridge. Remove the short black two core cable supplied with the fridge. The red wire will have a piggy back connector with a thinner red wire attached to it. Also remove this wire from the piggy back connector as in the photo.



You can now discard the short two core cable that was supplied with the fridge. Now fit the Travelvolts cable set to the control unit observing the correct polarity. Red to + and brown to -.

Next join the thin red wire from the control unit to the thin red wire on the Travelvolts cable set as per the photo. Secure the brown and red cables to the fridge body using cable ties to take the strain off the connectors. The black foam insulated pipe is a good place to do this.



Finally, connect the two ring terminals to your leisure battery, or to your fuse box if appropriate.

Cable set with switched relay

Complete as above and then run the twin red/black cable to where you want to mount the switch and cut to length. Fit the two red spades and attach them to the switch.

travelvolts.com accepts no liability for injury or damage caused by the incorrect fitment or use of this product

